








# TRANSPORT EQUIPMENT



## Guidelines to 2" fifth wheel selection

Picture	Type & features	Specifications	Applications
	<b><u>JSK3-2</u></b> Light weight Pressed steel Ex-import Provision for greasing	D-value = 22,5 kN GCM = 8 000kg Imposed load = 3 000 kg Weight = 35 kg Cardinal mount Height = 120mm	Light duty applications
	<b><u>JSK36DV2</u></b> Light weight Pressed steel Ex-stock Maintenance free pivot bearings	D-value = 152 kN GCM = 65 000kg Imposed load = 20 000 kg Weight = 117 kg Cardinal mount Height = 185mm	General on-road Good road conditions
	<b><u>JSK36C</u></b> Replaceable wear parts Cast steel Ex-stock Maintenance free rubber cushions	D-value = 152 kN GCM = 65 000kg Imposed load = 20 000 kg Weight = 157 kg Rubber mount Heights = 150 & 185mm	General applications (rear end tipper operations when blocking)
	<b><u>JSK37CW</u></b> Low maintenance Wearing ring insert Teflon wear pads SG iron Ex-stock Maintenance free rubber cushions	D-value = 152 kN GCM = 65 000kg Imposed load = 20 000 kg Weight = 152 kg Rubber mount Heights = 150 & 185mm	General on-road Dedicated combinations (Not suited to blocking)
	<b><u>JSK37C</u></b> Replaceable wear parts SG iron Ex-stock Maintenance free rubber cushions	D-value = 152 kN GCM = 65 000kg Imposed load = 20 000 kg Weight = 152 kg Rubber mount Heights = 150 & 185mm	General applications (Not suited to blocking)
	<b><u>JSK37E</u></b> Replaceable wear parts SG iron Ex-stock Maintenance free pivot bearings	D-value = 152 kN GCM = 65 000kg Imposed load = 20 000 kg Weight = 136 kg Cardinal mount Height = 150 & 185mm	On-road applications Good road conditions (Not suited to blocking)
	<b><u>SLE slider</u></b> Light weight Replaceable wear parts SG iron Weldable slider frame Ex-import Maintenance free pivot bearings	D-value = 152 kN GCM = 65 000kg Imposed load = 20 000 kg Weight = 233 kg Cardinal mount Height = 173mm	Load distribution on axles On-road applications (Not suited to blocking)